(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 9 June 2005 (09.06.2005)

PCT

(10) International Publication Number WO 2005/052509 A1

(51) International Patent Classification7: G06M 9/00

G01B 15/02.

(21) International Application Number:

PCT/JP2004/017670

(22) International Filing Date:

22 November 2004 (22.11.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-393248

25 November 2003 (25.11.2003)

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, Ohta-ku, Tokyo 146-8501 (JP).


(72) Inventors; and

(75) Inventors/Applicants (for US only): MIYAZAKI, Jungo [JP/JP]; c/o Canon Kabushiki Kaisha, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 146-8501 (JP). OUCHI, Toshihiko [JP/JP]; c/o Canon Kabushiki Kaisha, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 146-8501 (JP).

- (74) Agents: OKABE, Masao et al.; No. 602, Fuji Bldg., 2-3, Marunouchi 3-chome, Chiyoda-ku, Tokyo 100-0005 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB. GD, GE, GH, GM. HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR COUNTING THE NUMBER OF LAYERS OF A MULTILAYER OBJECT BY MEANS OF ELECTROMAGNETIC WAVES



respective interfaces of the layers are evaluated to count the number of layers. Alternatively, the phase of the electromagnetic wave transmitted through the multilayer object, is evaluated to determine the number of layers. It is proposed to use frequencies from 30 GHz to 100 THz, ic. microwaves, millimeter waves and infrared waves.